

LUKOIL GENESIS SPECIAL VL 0W-20

low-ash, synthetic high performance engine oil especially for VOLVO

APPROVALS

VOLVO VCC RBS0-2AE

MEETS REQUIREMENTS

ACEA C2 ACEA A1/B1 Fiat 9.55535 DSX

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL VL 0W-20 is a lowash, synthetic high performance engine oil, specially developed for "Fuel-Efficient Vehicles" of VOLVO. It combined smooth running characteristic with a maximum of fuel saving and highest possible power output of the engine

LUKOIL GENESIS SPECIAL VL 0W-20 has a best viscosity setup for smooth running engine oils and maximum fuel economy

LUKOIL GENESIS SPECIAL VL 0W-20 midSAPS technology provide lowest stress and long durability of particulate filter.

LUKOIL GENESIS SPECIAL VL 0W-20 guarantees through its latest additive technology a high keep clean effect of the engine, reduce friction in the engine and provide so high economy, optimal energy saving and lifetime

LUKOIL GENESIS SPECIAL VL 0W-20 excellent cold flow properties guarantee quick lubrication of the complete engine and reduces wear, especially during warm-up phase.

APPLICATION

LUKOIL GENESIS SPECIAL VL 0W-20 is a special developed product for VOLVO with required approval VOLVO VCC RBS0-2AE. Warning! This oil may be unsuitable for use in some engines. Consult owner manual or handbook if in doubt.


TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL VL 0W-20
Density/15°C	kg/m ³	DIN 51575	843
Flash point COC	°C	ISO 2592	230
Viscosity class		SAE J 300	0W-20
Viscosity/40°C	mm²/s	DIN 51562/T1	48,2
Viscosity/100°C	mm²/s	DIN 51562/T1	9,2
Viscosity index		DIN ISO 2909	177
Pour point	°C	DIN ISO 3016	<-40

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

1 September 2016, Page 1/1
* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com



+43(1)205 222-8800

www.lukoil-lubricants.eu

