



# 01000A Motor Oil 15W-50 Multigrade

Document version: November 29th 2017



## Description

This mineral motor oil has been specially developed for light duty petrol- and diesel engines of passenger cars. This motor oil is not suitable for turbo engines.

## According to the specifications of

API CD / SG

## Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 01001A   | 1 L    | 6              | 450              |
| 01020A   | 20 L   | 1              | 30               |
| 01020A   | 20 L   | 1              | 30               |
| 01060A   | 60 L   | 1              | -                |
| 01205A   | 205 L  | 1              | 2                |
| P01000A  | bulk   | 1              | -                |

## Typical characteristics

| TEST                         | METHOD     | VALUE  |                    |
|------------------------------|------------|--------|--------------------|
| SAE                          |            | 15W-50 |                    |
| Density at 15°C              | ASTM D4052 | 0,886  | kg/l               |
| Kinematic viscosity at 40°C  | ASTM D445  | 170    | mm <sup>2</sup> /s |
| Kinematic viscosity at 100°C | ASTM D445  | 18,4   | mm <sup>2</sup> /s |
| Viscosity index              | ASTM D2270 | 121    |                    |
| Dynamic viscosity at -15°C   | ASTM D5293 | 7800   | mPa·s              |
| Flashpoint COC               | ASTM D92   | 240    | °C                 |
| Pourpoint                    | ASTM D6892 | -33    | °C                 |