



04000AC Motor Oil 15W-40 Extra High Performance Diesel Truck

Document version: November 29th 2017

Description

This extra high performance diesel motor oil (ACEA E9) has been specially developed for use in modern, high output, low emission engines of commercial vehicles according to Euro 4, Euro 5 and Euro 6 emission standards and also gives excellent protection in older diesel engines. Important: This motor oil is absolutely not suitable for use in petrol engines.

According to the specifications of

ACEA E7 / E9
API CI-4 / CI-4+ / CJ-4 / SN
Caterpillar ECF-2 / ECF-3
Cummins CES 20081
Detroit Diesel 93K218
Deutz DQC III-10 LA
Global DHD-1
JASO DH-2
Mack EO-O Premium Plus
MAN M 3575
MB-Approval 228.31
MTU Type 2.1
Renault RLD-3
Volvo VDS-3 / VDS-4

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04020AC	20 L	1	30
04060AC	60 L	1	12
04205AC	205 L	1	2
04999AC	1000 L	1	-
P04000AC	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,870	kg/l
Kinematic viscosity at 40°C	113.0	mm ² /s
Kinematic viscosity at 100°C	13.8	mm ² /s
Viscosity index	139	
Dynamic viscosity at -20°C	6400	mPa·s
Flashpoint COC	225	°C
Pourpoint	-36	°C
Total Base number	8.0	mgKOH/g
Sulphated ash	1.0	mass%