



04000A Motor Oil 10W-40 Super High Performance Diesel Truck

Document version: November 29th 2017

Description

This high-grade semi synthetic motor oil has been specially developed for diesel engines of commercial vehicles. In addition this motor oil has been formulated to make long oil-change intervals possible and to prevent bore polishing.

According to the specifications of

ACEA B3 / B4 / E5 / E7
Allison C4
API CF-4 / CG-4 / CH-4 / CI-4
Cummins CES 20076 / CES 20077 / CES 20078
Detroit Diesel 93K215
Deutz DQC III-10
Global DHD-1
JASO DH-1
Mack EO-M Plus / EO-N
MAN M 3275
MB-Approval 228.3
MTU Type 2
Renault RLD / RLD-2
Volvo VDS-3

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04020A	20 L	1	30
04060A	60 L	1	12
04205A	205 L	1	2
04999A	1000 L	1	-
P04000A	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,872	kg/l
Kinematic viscosity at 40°C	86.0	mm ² /s
Kinematic viscosity at 100°C	13.1	mm ² /s
Viscosity index	153	
Dynamic viscosity at -25°C	5900	mPa·s
Flashpoint COC	243	°C
Pourpoint	-42	°C
Total Base number	11.9	mgKOH/g
Sulphated ash	1.9	mass%