



# 04000E Motor Oil 5W-30 Semi Synthetic Fuel Conserving

Document version: November 29th 2017



## Description

This semi synthetic fuel-conserving motor oil has been specially developed for all Ford and Mazda cars constructed up to 2008, among others. This motor oil offers optimum protection for petrol, LPG and diesel engines where the ACEA A1/B1 specification is required.

## According to the specifications of

ACEA A1/B1  
 API CF / SL  
 Ford WSS-M2C912-A / WSS-M2C913-A / WSS-M2C913-B  
 ILSAC GF-3

## Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04001E	1 L	6	450
04004E	4 L	4	112
04005E	5 L	4	112
04020E	20 L	1	30
04060E	60 L	1	12
04200E	200 L	1	-
04205E	205 L	1	2
04999E	1000 L	1	-
P04000E	bulk	1	-

## Typical characteristics

TEST	VALUE	
Density at 15°C	0,852	kg/l
Kinematic viscosity at 40°C	56.0	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	10.0	mm <sup>2</sup> /s
Viscosity index	167	
Dynamic viscosity at -30°C	4750	mPa·s
Flashpoint COC	230	°C
Pourpoint	-39	°C
Total Base number	10.4	mgKOH/g
High Temperature / High Share	3.0	mPa·s