



04000S Motor Oil 10W-40 Semi Synthetic SN

Document version: November 29th 2017



Description

This semi synthetic motor oil is designed for lubrication of four stroke petrol and diesel engines. The formulation is based on highly refined base oils and the high quality ensures excellent engine protection and durability with very good low temperature fluidity.

According to the specifications of

ACEA A3/B4
API CF / SN
MB-Approval 229.1

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04001S	1 L	6	450
04004S	4 L	4	112
04005S	5 L	4	112
04020S	20 L	1	30
04060S	60 L	1	12
04205S	205 L	1	2
04999S	1000 L	1	-
P04000S	bulk	1	-

Typical characteristics

TEST	METHOD	VALUE	
Density at 15°C	ASTM D4052	0,875	kg/l
Kinematic viscosity at 40°C	ASTM D445	93	mm ² /s
Kinematic viscosity at 100°C	ASTM D445	13,9	mm ² /s
Viscosity index	ASTM D2270	153	
Dynamic viscosity at -25°C	ASTM D5293	6820	mPa·s
Flashpoint COC	ASTM D92	220	°C
Pourpoint	ASTM D6892	-39	°C
Total Base number	ASTM D2896	8,4	mgKOH/g
Sulphated ash	ASTM D874	1,03	mass%