



## 04000 Motor Oil 10W-40 Semi Synthetic

Document version: November 29th 2017



### Description

This semi synthetic universal motor oil has been developed for normal duty petrol, LPG and diesel engines of cars and light commercial vehicles.

### According to the specifications of

ACEA A3/B4  
API CF / SL  
MB-Approval 229.1  
VW 501.01 / 505.00

### Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04001	1 L	6	450
04004	4 L	4	112
04005	5 L	4	112
04020	20 L	1	30
04060	60 L	1	12
04200	200 L	1	-
04205	205 L	1	2
04999	1000 L	1	-
P04000	bulk	1	-

## Typical characteristics

TEST	VALUE	
Density at 15°C	0,866	kg/l
Kinematic viscosity at 40°C	97.0	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	14.1	mm <sup>2</sup> /s
Viscosity index	150	
Dynamic viscosity at -25°C	6000	mPa·s
Flashpoint COC	220	°C
Pourpoint	-39	°C
Total Base number	7.9	mgKOH/g
Sulphated ash	1.0	mass%
Noack evaporation loss	12.8	mass%