



05000AB Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel

Document version: November 29th 2017



Description

This motor oil (ACEA E6) has been specially developed for all Euro 4, Euro 5 and certain Euro 6 diesel engines of commercial vehicles that are fitted with a DPF filter and use low sulphur (<50 ppm) diesel fuel operating under the most extreme operating conditions. This motor oil is suitable for extended oil-change intervals (80,000 – 120,000 km) taking into account the instructions for use. This motor oil is also suitable for use in so-called EGR engines with or without particle filter. This motor oil is absolutely not suitable for use in petrol engines.

According to the specifications of

ACEA E6 / E7
API CI-4
Cummins CES 20076 / CES 20077
DAF
Deutz DQC III-10 LA
JASO DH-2
Mack EO-N
MAN M 3271-1 / M 3477
MB-Approval 226.9 / 228.51
MTU Type 3.1
Renault RLD-2 / RXD
Volvo RGD / VDS-3

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05005AB	5 L	4	112
05020AB	20 L	1	30
05060AB	60 L	1	12
05205AB	205 L	1	2
05999AB	1000 L	1	-
P05000AB	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,868	kg/l
Kinematic viscosity at 40°C	86.9	mm ² /s
Kinematic viscosity at 100°C	13.3	mm ² /s
Viscosity index	156	
Dynamic viscosity at -25°C	6100	mPa·s
Flashpoint COC	230	°C
Pourpoint	-39	°C
Total Base number	12.5	mgKOH/g
Sulphated ash	1.0	mass%
Noack evaporation loss	10.5	mass%