



05000A Motor Oil 10W-40 Premium Synthetic Diesel

Document version: November 29th 2017



Description

This premium synthetic diesel motor oil is a fully synthetic engine oil. It provides superior protection for most Euro 4, Euro 5 and the latest Scania Euro 6 high-performance diesel engines. Recommended in a wide range of heavy duty applications, suitable for on-road and off-road transport, construction and agricultural industries. This 'long-drain' oil is specially developed for Scania engines which require the LDF-3 specification.

According to the specifications of

ACEA E4 / E7
API CI-4
Cummins CES 20072
DAF Extended drain
Deutz DQC III-10
Mack EO-N
MAN M 3277
MB-Approval 228.5
MTU Type 3
Renault RD-2 / RLD / RLD-2 / RXD
Scania LDF-2 / LDF-3
Volvo VDS-3

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001A	1 L	6	450
05005A	5 L	4	112
05020A	20 L	1	30
05060A	60 L	1	12
05205A	205 L	1	2
05999A	1000 L	1	-
P05000A	bulk	1	-

Typical characteristics

TEST	VALUE	
SAE	10W-40	
Density at 15°C	0,870	kg/l
Kinematic viscosity at 40°C	86,3	mm ² /s
Kinematic viscosity at 100°C	13,3	mm ² /s
Viscosity index	155	
Flashpoint COC	220	°C
Pourpoint	-39	°C
Total Base number	16,1	mgKOH/g