



## 05000DPF Motor Oil 5W-30 Premium Synthetic C3 DPF

Document version: November 29th 2017



### Description

This premium synthetic motor oil has been specially developed for BMW and Mercedes-Benz engines. This motor oil has the approvals of BMW Long Life 04 and Mercedes-Benz Long Life 229.51. This motor oil is also suitable for Euro 4 and Euro 5 engines. This SAE 5W-30 motor oil with ACEA C3 standard is recommended for petrol and diesel engines fitted with exhaust gas after-treatment systems.

### According to the specifications of

ACEA C3  
API CF / SN  
BMW LL-04  
MB-Approval 229.51 / 229.52  
Opel/GM dexos2™  
VW 502.00 / 505.00

## Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001DPF	1 L	6	450
05005DPF	5 L	4	112
05020DPF	20 L	1	30
05060DPF	60 L	1	12
05205DPF	205 L	1	2
05999DPF	1000 L	1	-
P05000DPF	bulk	1	-

## Typical characteristics

TEST	VALUE	
Density at 15°C	0,855	kg/l
Kinematic viscosity at 40°C	74.3	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	12.4	mm <sup>2</sup> /s
Viscosity index	166	
Dynamic viscosity at -30°C	6060	mPa·s
Flashpoint COC	230	°C
Pourpoint	-39	°C
Total Base number	7,6	mgKOH/g
Sulphated ash	0.8	mass%
High Temperature / High Share	0	mPa·s
Noack evaporation loss	0	mass%