



## 05000DX1-FE Motor Oil 5W-20 Premium Synthetic DX1 Fuel Economy

Document version: November 29th 2017



### Description

This MPM premium synthetic motor oil is specially formulated to meet the latest requirements for petrol engines of passenger cars, light commercial vehicles and SUVs. Particularly developed for the American and Asian markets. This fully synthetic engine oil offers total engine protection and keeps the engine clean even under the most severe conditions. Due to the good friction properties, MPG is enhanced. In addition, because of the excellent thin-flowability, this engine oil offers excellent cold start properties.

### According to the specifications of

API SN  
Chrysler MS-6395  
Ford WSS-M2C945-A  
ILSAC GF-5  
Opel/GM dexos1™ Gen 2

## Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001DX1-FE	1 L	6	450
05004DX1-FE	4 L	4	112
05005DX1-FE	5 L	4	112
05020DX1-FE	20 L	1	30
05060DX1-FE	60 L	1	12
05205DX1-FE	205 L	1	2
05999DX1-FE	1000 L	1	-
P05000DX1-FE	bulk	1	-

## Typical characteristics

TEST	METHOD	VALUE	
SAE		5W-20	
Density at 15°C	ASTM D4052	0.852	kg/l
Kinematic viscosity at 40°C	ASTM D445	48.9	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	ASTM D445	8.72	mm <sup>2</sup> /s
Viscosity index	ASTM D2270	158	
Flashpoint COC	ASTM D92	228	°C
Pourpoint	ASTM D97	-42	°C
Total Base number	ASTM D2896	9.2	mgKOH/g
Sulphated ash	ASTM D874	0.88	mass%