



05000EDT Motor Oil 0W-30 Premium Synthetic EDT

Document version: November 29th 2017



Description

This MPM premium synthetic Motor oil has been specially developed for use in Ford Duratorq TDCi Euro 6 engines and prescribed as mandatory for these engines fitted with exhaust gas after-treatment systems and turbochargers. Due to the balanced formulation and carefully selected additive package contained within, this oil is recommended and suitable for Duratorq Euro 6 engines with extended drain intervals, low CO₂ emissions and high fuel-saving features. This high performance engine oil is also suitable for vehicles where the SAE 0W-30 with ACEA C2 specification is requested.

According to the specifications of

ACEA C2
Ford WSS-M2C950-A

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001EDT	1 L	6	450
05005EDT	5 L	4	112
05020EDT	20 L	1	30
05060EDT	60 L	1	12
05205EDT	205 L	1	2
05999EDT	1000 L	1	-
P05000EDT	bulk	1	-

Typical characteristics

TEST	METHOD	VALUE	
SAE		0W-30	
Density at 15°C	ASTM D4052	0.847	kg/l
Kinematic viscosity at 40°C	ASTM D445	48.0	mm ² /s
Kinematic viscosity at 100°C	ASTM D445	9.8	mm ² /s
Viscosity index	ASTM D2270	196	
Dynamic viscosity at -35°C	ASTM D5293	5600	mPa·s
Flashpoint COC	ASTM D92	210	°C
Pourpoint	ASTM D7346	-48	°C
Total Base number	ASTM D2896	7.8	mgKOH/g
Sulphated ash	ASTM D874	0.79	mass%