



05000EF Motor Oil 5W-30 Premium Synthetic C1 Mazda / Jaguar

Document version: November 29th 2017



Description

This synthetic top quality 'Low SAPS' Long Life motor oil has been specially developed for petrol and diesel engines where SAE 5W-30 with ACEA C1 standard is required and equipped with an exhaust gas after-treatment system. This motor oil is recommended for various cars such as Mazda, Jaguar and Land Rover.

According to the specifications of

ACEA C1
Ford WSS-M2C934-B
JASO DL-1
Mazda Service Fill

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001EF	1 L	6	450
05005EF	5 L	4	112
05020EF	20 L	1	30
05060EF	60 L	1	12
05205EF	205 L	1	2
05999EF	1000 L	1	-
P05000EF	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,848	kg/l
Kinematic viscosity at 40°C	55,6	mm ² /s
Kinematic viscosity at 100°C	10,00	mm ² /s
Viscosity index	169	
Dynamic viscosity at -30°C	4000	mPa·s
Flashpoint COC	226	°C
Pourpoint	-36	°C
Total Base number	7,8	mgKOH/g
Sulphated ash	0,5	mass%
High Temperature / High Share	2,9	mPa·s