



05000E Motor Oil 5W-30 Premium Synthetic Fuel Conserving Ford

Document version: November 29th 2017



Description

This premium synthetic fuel-saving motor oil with Ford M2C913-C/D specification has been specially developed for all Ford passenger cars and light commercial vehicles. This motor oil offers optimum protection for diesel, petrol and LPG engines. This motor oil is also suitable for vehicles where SAE 5W-30 with the ACEA A5/B5 specification is required.

According to the specifications of

ACEA A5/B5
API CF / SN
Ford WSS-M2C913-C / WSS-M2C913-D

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001E	1 L	6	450
05005E	5 L	4	112
05020E	20 L	1	30
05060E	60 L	1	12
05205E	205 L	1	2
05999E	1000 L	1	-
P05000E	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,852	kg/l
Kinematic viscosity at 40°C	53,30	mm ² /s
Kinematic viscosity at 100°C	9,66	mm ² /s
Viscosity index	168	
Flashpoint COC	220	°C
Pourpoint	-45	°C
Total Base number	10,1	mgKOH/g
Sulphated ash	1,09	mass%