



05000GM Motor Oil 5W-30 Premium Synthetic GM / Opel

Document version: November 29th 2017



Description

This premium synthetic Long Life fuel-conserving motor oil has been specially developed for the GM/Opel petrol and diesel engines with flexible maintenance systems according to GM-LL-A-025 and LL-B-025 specifications from between model year 2000 and 2009.

According to the specifications of

ACEA A3/B4
API CF / SL
Opel/GM GM-LL-A-025 / GM-LL-B-025

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001GM	1 L	6	450
05005GM	5 L	4	112
05020GM	20 L	1	30
05060GM	60 L	1	12
05205GM	205 L	1	2
05999GM	1000 L	1	-
P05000GM	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,855	kg/l
Kinematic viscosity at 40°C	69.0	mm ² /s
Kinematic viscosity at 100°C	11.7	mm ² /s
Viscosity index	166	
Dynamic viscosity at -30°C	5910	mPa·s
Flashpoint COC	232	°C
Pourpoint	-39	°C
Total Base number	10.5	mgKOH/g
Sulphated ash	1.35	mass%
Noack evaporation loss	11.3	mass%