



# 05000JP Motor Oil 0W-20 Premium Synthetic RC

Document version: November 29th 2017



## Description

This premium synthetic motor oil SAE 0W-20 has been specially developed for high-tech engines of Japanese, USA and European cars manufacturers and ensures an extremely economical fuel consumption. Due to the organic, friction-reducing additives contained within, this oil reduces motor wear to the minimum. This oil has a very low viscosity of SAE 0W-20. Note: The use of this oil in motors designed for motor oil with a high viscosity may result in insufficient oil circulation, leaks and other problems.

## According to the specifications of

API SN  
ILSAC GF-5

## Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001JP	1 L	6	450
05005JP	5 L	4	112
05020JP	20 L	1	30
05060JP	60 L	1	12
05205JP	205 L	1	2
05999JP	1000 L	1	-
P05000JP	bulk	1	-

## Typical characteristics

TEST	VALUE	
Density at 15°C	0,854	kg/l
Kinematic viscosity at 40°C	41,5	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	8,5	mm <sup>2</sup> /s
Viscosity index	199	
Flashpoint COC	230	°C
Pourpoint	-45	°C
Total Base number	5,1	mgKOH/g