



05000S Motor Oil 5W-50 Premium Synthetic SN

Document version: November 29th 2017

Description

This premium synthetic engine oil has been specially developed for the perfect lubrication of high performance and high powered petrol and diesel engines with or without a turbocharger. The formulation provides excellent protection against friction and ensures superior lubricating oil film at high speeds.

According to the specifications of

ACEA A3/B4
API CF / SN

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001S	1 L	6	450
05005S	5 L	4	112
05020S	20 L	1	30
05060S	60 L	1	12
05205S	205 L	1	2
05999S	1000 L	1	-
P05000S	bulk	1	-

Typical characteristics

TEST	METHOD	VALUE	
SAE		5W-50	
Density at 15°C	ASTM D4052	0,852	kg/l
Kinematic viscosity at 40°C	ASTM D445	118	mm ² /s
Kinematic viscosity at 100°C	ASTM D445	18	mm ² /s
Viscosity index	ASTM D2270	170	
Dynamic viscosity at -30°C	ASTM D5293	6200	mPa·s
Flashpoint COC	ASTM D92	235	°C
Pourpoint	ASTM D6892	-30	°C
Total Base number	ASTM D2896	9,6	mgKOH/g
Sulphated ash	ASTM D874	1,1	mass%