



## 05000 Motor Oil 5W-40 Premium Synthetic

Document version: November 29th 2017



### Description

This universal premium synthetic motor oil has been developed for modern petrol and diesel engines in cars and light commercial vehicles and meets the requirements of all leading car manufacturers.

### According to the specifications of

ACEA A3/B4  
API CF / SN  
BMW LL-01  
MB-Approval 229.3  
Opel/GM GM-LL-B-025  
Porsche A40  
PSA B71 2296  
Renault RN 0700 / RN 0710  
VW 502.00 / 505.00

## Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001	1 L	6	450
05004	4 L	4	112
05005	5 L	4	112
05020	20 L	1	30
05060	60 L	1	12
05205	205 L	1	2
05999	1000 L	1	-
P05000	bulk	1	-

## Typical characteristics

TEST	VALUE	
Density at 15°C	0,856	kg/l
Kinematic viscosity at 40°C	86,0	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	14,4	mm <sup>2</sup> /s
Viscosity index	175	
Dynamic viscosity at -30°C	6100	mPa·s
Flashpoint COC	220	°C
Pourpoint	-42	°C
Total Base number	9,6	mgKOH/g
Sulphated ash	1,2	mass%
High Temperature / High Share	0	mPa·s
Noack evaporation loss	0	mass%