



16000HT Automatic Transmission Fluid High Torque

Document version: 15 June 2017



| Art. no. | Volume | Items per unit | Items per pallet |
|----------|--------|----------------|------------------|
| 16001HT | 1 L | 6 | 450 |
| 16004HT | 4 L | 4 | 112 |
| 16020HT | 20 L | 1 | 30 |
| 16060HT | 60 L | 1 | 12 |
| 16205HT | 205 L | 1 | 2 |
| 16999HT | 1000 L | 1 | 0 |
| P16000HT | bulk | 1 | 0 |

Description

This automatic transmission fluid has been specially designed for modern Aisin Warner transmissions with AW-1 recommendation and in Jatco transmissions. Thanks to the well balanced additive package, this automatic transmission fluid has excellent friction properties and shifting performance. This liquid also has durable anti-shudder properties.

Specifications

Aisin Warner AW-1
Fiat 9.55550-AV2
Ford M2C922-A1
JATCO 3100 PL085 / FWD (N402) / JF506E (K17)
VW G 052 990

Typical characteristics

| | | |
|------------------------------|------------|--------------------|
| Density at 15°C | 0,852 | kg/l |
| Colour | Dark brown | |
| Kinematic viscosity at 40°C | 37,3 | mm ² /s |
| Kinematic viscosity at 100°C | 7,3 | mm ² /s |
| Viscosity index | 165 | |
| Dynamic viscosity at -40°C | 17000 | mPa·s |
| Flashpoint COC | 216 | °C |
| Pourpoint | -43 | °C |