



16000 ATF Automatic Transmission Fluid Dexron III F/G

Document version: 13 June 2017



Art. no.	Volume	Items per unit	Items per pallet
16001	1 L	6	450
16004	4 L	4	112
16020	20 L	1	30
16060	60 L	1	12
16205	205 L	1	2
16999	1000 L	1	0
P16000	bulk	1	0

Description

This premium synthetic ATF Dexron III F/G automatic transmission oil has been specially developed for automatic transmissions, power steering, torque converters and other applications for which manufacturers specify an ATF Dexron III F/G oil.

Specifications

Allison C4
Ford ESP-M2C138-CJ / ESP-M2C166-H / M2C186-A / Mercon
GM Dexron III F / Dexron III G
MAN 339 Type V1 / 339 Type Z1
MB-Approval 236.9
Nissan ECVT
Voith H55.6335xx
Volvo STD 1273.41 (97341)
ZF TE-ML 03D / 04D / 09 / 11B / 14A / 17C

Typical characteristics

Density at 15°C	0,855	kg/l
Colour	red	
Kinematic viscosity at 40°C	34.3	mm ² /s
Kinematic viscosity at 100°C	7.7	mm ² /s
Viscosity index	205	
Flashpoint COC	196	°C
Pourpoint	-45	°C
Brookfield viscosity at -40°C	18400	mPa·s