



20000LV Brake Fluid Low Viscosity DOT 4+ LV

Document version: November 29th 2017



Description

This synthetic DOT 4+ Low Viscosity brake fluid has been specially developed for use in all hydraulically operated brake systems for which constructors specify a brake fluid of the type DOT 4+ Low Viscosity. This brake fluid is extremely suitable for brake systems with ESP and ABS systems.

According to the specifications of

FMVSS 116 DOT 4
ISO 4925 Class 6

Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 20001LV | 1 L | 6 | 450 |
| 20005LV | 5 L | 4 | 160 |
| 20020LV | 20 L | 1 | 30 |
| 20060LV | 60 L | 1 | 12 |
| 20205LV | 205 L | 1 | 2 |
| 20999LV | 1000 L | 1 | - |
| P20000LV | bulk | 1 | - |

Typical characteristics

| TEST | VALUE | |
|------------------------------|--------|--------------------|
| Density at 20°C | 1,06 | kg/l |
| Colour | yellow | |
| Kinematic viscosity at -40°C | 650 | mm ² /s |
| Kinematic viscosity at 100°C | 2.1 | mm ² /s |
| PH | 7.5 | |
| Wet boiling point | 178 | °C |
| Boiling point | 272 | °C |