



## 39000F Industrial Gear Oil 320

Document version: November 29th 2017



### Description

This mineral industrial gearbox oil 320 has been specially developed for use in sealed gearboxes, equipped with straight, spiral, conical and worm gears.

### According to the specifications of

AGMA 9005-E02  
AISE 224  
DAVID BROWN S1.53.101E  
DIN 51517 part 3 CLP

### Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 39001F   | 1 L    | 6              | 450              |
| 39005F   | 5 L    | 4              | 112              |
| 39020F   | 20 L   | 1              | 30               |
| 39060F   | 60 L   | 1              | 12               |
| 39205F   | 205 L  | 1              | 2                |
| 39999F   | 1000 L | 1              | -                |
| P39000F  | bulk   | 1              | -                |

## Typical characteristics

| TEST                         | VALUE |                    |
|------------------------------|-------|--------------------|
| Density at 15°C              | 0,900 | kg/l               |
| Kinematic viscosity at 40°C  | 330   | mm <sup>2</sup> /s |
| Kinematic viscosity at 100°C | 24.2  | mm <sup>2</sup> /s |
| Viscosity index              | 94    |                    |
| Flashpoint COC               | 255   | °C                 |
| Pourpoint                    | -21   | °C                 |
| Total Acid number            | 0.38  | mgKOH/g            |
| FZG A/16,6/140               | 12    | level              |