



41000D Motor Oil SAE 40 Super Single Grade

Document version: November 29th 2017



Description

This mineral SAE 40 SF/CD Super Single Grade oil has been developed for a wide range of purposes and is extremely suitable for stationary engines, for industrial transmissions and for hydraulic systems.

According to the specifications of

API CD / SF
CCMC D1
CCMC G2

Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 41001D | 1 L | 6 | 450 |
| 41005D | 5 L | 4 | 112 |
| 41020D | 20 L | 1 | 30 |
| 41060D | 60 L | 1 | 12 |
| 41205D | 205 L | 1 | 2 |
| 41999D | 1000 L | 1 | - |
| P41000D | bulk | 1 | - |

Typical characteristics

| TEST | VALUE | |
|------------------------------|-------|--------------------|
| Density at 15°C | 0,896 | kg/l |
| Kinematic viscosity at 40°C | 152 | mm ² /s |
| Kinematic viscosity at 100°C | 14.6 | mm ² /s |
| Viscosity index | 94 | |
| Flashpoint COC | 245 | °C |
| Pourpoint | -9 | °C |
| Total Base number | 4.4 | mgKOH/g |
| Sulphated ash | 0.76 | mass% |