

43000 2-Stroke Oil Synthetic TC+

Document version: November 29th 2017



Description

According to the specifications of

Packing units

This TC+ synthetic high-grade 2-stroke oil has been specially developed for use in modern air- and/or water-cooled 2-stroke engines. This 2-stroke oil is self-mixing and extremely suitable for engines with oil-injection systems.

API TC+ ISO LEGD JASO FC (low smoke) Piaggio SL TISI

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
43001	1 L	6	450
43005	5 L	4	112
43020	20 L	1	30
43060	60 L	1	12
43205	205 L	1	2
43999	1000 L	1	-
P43000	bulk	1	-

Page 1/2

Typica	har	ad	lori	cti	<u></u>
rypicu	iui	uci		511	CS

TEST

1	1	٨	1	1.1	
	ν.	μ	۱L	U	

Density at 15°C	0,882	kg/l
Colour	Yellowbrown	
Kinematic viscosity at 40°C	78.4	mm²/s
Kinematic viscosity at 100°C	10.2	mm²/s
Viscosity index	112	
Flashpoint COC	100	°C
Pourpoint	-15	°C
Total Base number	1.1	mgKOH/g
Sulphated ash	0.28	mass%

Page 2/2