



49000 Vacuum Pump Oil ISO VG 100

Document version: November 29th 2017

Description

The vacuum pump oil is a mineral oil with anti wear, corrosion, oxidation and foaming additives. This oil is perfectly suitable for the use in vacuum pumps, tool machinery and other hydraulic applications where the requirement ISO VG 100 is. This oil is recommended by brands like Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco, Worthington etc.

According to the specifications of

AFNOR NF E 48-603 HM / NF E 48-690 / NF E 48-691
Denison HF-2
DIN 51524 Part 2 HLP
Eaton Vickers I-286-S / M-2950-S
ISO 11158 HM / 6743-4 HM

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
49020	20 L	1	30
49060	60 L	1	12
49205	205 L	1	2
49999	1000 L	1	-
P49000	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,883	kg/l
Kinematic viscosity at 40°C	101	mm ² /s
Kinematic viscosity at 100°C	11,4	mm ² /s
Viscosity index	99	
Flashpoint COC	232	°C
Pourpoint	-24	°C
Total Acid number	0,36	mgKOH/g
ISO VG class	100	