



# 52000B 4-Stroke Motorcycle Oil 15W-50 Semi Synthetic

Document version: November 29th 2017

## Description

This 15W-50 semi synthetic 4-stroke motorcycle oil has been specially developed for optimum lubrication of 4-stroke motorcycle engines. The special formulation ensures excellent cleaning and is suitable for lubrication of gearboxes with or without wet plate clutches.

## According to the specifications of

API SL  
JASO MA / MA2

## Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 52001B   | 1 L    | 6              | 450              |
| 52020B   | 20 L   | 1              | 30               |
| 52060B   | 60 L   | 1              | 12               |
| 52205B   | 205 L  | 1              | 2                |
| P52000B  | bulk   | 1              | -                |

## Typical characteristics

| TEST                         | METHOD     | VALUE  |                    |
|------------------------------|------------|--------|--------------------|
| SAE                          |            | 15W-50 |                    |
| Density at 15°C              | ASTM D4052 | 0.876  | kg/l               |
| Kinematic viscosity at 40°C  | ASTM D445  | 134    | mm <sup>2</sup> /s |
| Kinematic viscosity at 100°C | ASTM D445  | 17.6   | mm <sup>2</sup> /s |
| Viscosity index              | ASTM D2270 | 145    |                    |
| Dynamic viscosity at -20°C   | ASTM D5293 | 6500   | mPa·s              |
| Flashpoint COC               | ASTM D92   | 237    | °C                 |
| Pourpoint                    | ASTM D97   | -36    | °C                 |
| Total Base number            | ASTM D2986 | 7.0    | mgKOH/g            |