



56000 4-Stroke Motorcycle Oil 5W-50 Premium Synthetic Racing

Document version: November 29th 2017



Description

This premium synthetic 4-stroke motorcycle oil SAE 5W-50 has been specially developed for optimum lubrication of high-performance air- and water-cooled 4-stroke engines subject to the most stringent requirements. This oil is extremely suitable for very high revolutions and high loads and is also suitable for lubrication of gearboxes with a possible wet plate clutch.

According to the specifications of

API SL
JASO MA / MA2

Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 56001 | 1 L | 6 | 450 |
| 56020 | 20 L | 1 | 30 |
| 56060 | 60 L | 1 | 12 |
| 56205 | 205 L | 1 | 2 |
| 56999 | 1000 L | 1 | - |
| P56000 | bulk | 1 | - |

Typical characteristics

| TEST | VALUE | |
|------------------------------|--------|--------------------|
| Density at 15°C | 0,848 | kg/l |
| Kinematic viscosity at 40°C | 113.00 | mm ² /s |
| Kinematic viscosity at 100°C | 18.0 | mm ² /s |
| Viscosity index | 171 | |
| Dynamic viscosity at -30°C | 6000 | mPa·s |
| Flashpoint COC | 232 | °C |
| Pourpoint | -42 | °C |
| Total Base number | 7.7 | mgKOH/g |
| Sulphated ash | 0.94 | mass% |