



65000A Lithium Calcium grease EP-2

Document version: November 29th 2017



Description

This lithium calcium EP-2 Grease has been specially developed for chassis points and ball clutches and universal joints. This grease reduces the number of re-lubrication operations for commercial vehicles, earth-moving machinery and agricultural machinery. Due to the water-repellent properties this grease is excellent for use in damp and dirty conditions.

According to the specifications of

DIN 51502
ISO 6743 / L-XBC IB2
KP2K-20

Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 65000A | 0.4 kg | 12 | 1200 |
| 65500A | 0.5 kg | 6 | - |
| 65001A | 1 kg | 6 | - |
| 65018A | 18 kg | 1 | 28 |
| 65050A | 50 kg | 1 | 12 |
| 65185A | 185 kg | 1 | 2 |

Typical characteristics

| TEST | VALUE |
|-----------------------------|------------------------|
| Base oil | mineral |
| Colour | red |
| Kinematic viscosity at 40°C | 100 mm ² /s |
| NLGI class | 2 |
| Temperature range | -20 / 120 °C |
| Soap thickener | Lithium-Calcium |