



19000 Brake Fluid DOT 3

Document version: November 29th 2017



Description

This DOT-3 brake fluid has been specially developed for use in all hydraulically operated brake and clutch systems fitted with drum or disk brakes and for which constructors specify a DOT-3 type brake fluid.

According to the specifications of

FMVSS 116 DOT 3
ISO 4925
SAE J 1703

Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 19250 | 0.25 L | 12 | 2016 |
| 19485 | 0.5 L | 12 | 864 |
| 19005 | 5 L | 4 | 112 |
| 19020 | 20 L | 1 | 30 |
| 19060 | 60 L | 1 | 12 |
| 19205 | 205 L | 1 | 2 |
| 19999 | 1000 L | 1 | - |
| P19000 | bulk | 1 | - |

Typical characteristics

| TEST | VALUE | |
|------------------------------|--------|--------------------|
| Density at 20°C | 1,03 | kg/l |
| Colour | yellow | |
| Kinematic viscosity at -40°C | 1300 | mm ² /s |
| Kinematic viscosity at 100°C | 2.0 | mm ² /s |
| Flashpoint COC | 150 | °C |
| PH | 10 | |
| Wet boiling point | 145 | °C |
| Boiling point | 237 | °C |