



AD15000 Automatic Transmission Flush

Document version: November 29th 2017



Description

MPM automatic transmission flush is used to flush and clean the internal components of the ATF system. These highly effective cleaning properties reduce and remove sludge build up and unclog fluid passages within the ATF system.

Main benefits

- Eases and smoothens shifting.
- Unclogs fluid passages.
- Cleans deposits and varnish from clutch plates.
- Reduces wear and shift delay, increases transmission life and eliminating judder.

Application

Compatible with all transmission fluids.

Appliance instruction

- Prior to transmission fluid change (with or without a flush machine) add the contents of one 250 ml bottle to the automatic transmission or ATF flush machine.
- Let the engine run and shift between all gears for at least 15 minutes to circulate the product.
- Drain, flush and refill the transmission fluid from the automatic transmission by following the OEM procedure.

The contents of one 250ml bottle is suitable to treat an automatic transmission

system of up to 8 liters.

Always use the OEM recommend ATF fluid when refilling.

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
AD15250	0.25 L	6	1548
AD15999	1000 L	1	-

Typical characteristics

TEST	VALUE	
Density at 20°C	0,881	kg/l
Colour	amber	
Kinematic viscosity at 40°C	5,20	mm ² /s
Flashpoint PM	140	°C
Pourpoint	-57	°C