



## BLO34000 Marine Engine Oil HPE 15W-40

Document version: November 29th 2017



### Description

This high performance (HPE) multigrade diesel engine oil is specially designed for the lubrication of high-speed marine engines operating under severe conditions and under all weather conditions. The high quality base oils combined with superior additives, provides maximum oil drain intervals with excellent protection against wear and soot in either turbocharged or naturally-aspirated engines ensure maximum engine life and reduces maintenance costs.

### According to the specifications of

API CI-4  
Caterpillar ECF-1a  
Cummins CES 20076 / CES 20077 / CES 20078  
DAF  
Deutz DQC III-10  
Kubota  
MAN M 3275  
MB-Approval 228.3  
Mitsubishi  
Perkins  
Vetus  
Volvo VDS-3  
Yanmar

## Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BLO34001	1 L	6	450
BLO34005	5 L	4	112
BLO34020	20 L	1	30
BLO34060	60 L	1	12
BLO34205	205 L	1	2
BLO34999	1000 L	1	-
PBL034000	bulk	1	-

## Typical characteristics

TEST	VALUE	
SAE	15W-40	
Density at 15°C	0,885	kg/l
Kinematic viscosity at 40°C	100,0	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	14,0	mm <sup>2</sup> /s
Viscosity index	135	
Dynamic viscosity at -20°C	6500	mPa·s
Flashpoint COC	220	°C
Pourpoint	-36	°C
Total Base number	10,7	mgKOH/g
Sulphated ash	1,34	mass%