28.11.2025
v2

Technical Data for:

MARA POWER SCOOTER 2T

Description:
MARA POWER SCOOTER 2T is semi-synthetic engine oil designed for high protection of two-stroke scooter engines. Protects scooter engines in all weather conditions and guarantees maximum performance output of the scooter. This oil can be used for pre-mix, or with oil injection systems.

Benefits:
- Provides consistent lubrication during frequent starts and stops, ideal for city commuting
- Reduces engine noise and vibrations, improving ride comfort for scooters
- Improves engine efficiency by reducing friction
- Reduces carbon deposits, keeping the engine clean and maintaining performance over time

Specifications and approvals:
API TC
JASO FD
ISO EGD

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,87-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	55-80
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	9,2-11,4
Viscosity index	ASTM D 2270	-	> 140
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 130

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.