28.11.2025
v2

Technical Data for:

MARA EVOLUTION C2 0W-30

Description:
MARA EVOLUTION C2 0W-30 is fully synthetic oil for PSA EURO VI Blue HDi DW10F engines with exhaust aftertreatment and turbocharger. Offers high fuel economy, low CO2 emissions, excellent cold-start fluidity, engine cleanliness, and aftertreatment system protection. Suitable for vehicles with Stop & Start technology.

Benefits:
- Excellent wear resistance, extending engine life
- Helps reduce emissions due to its energy-conserving properties
- Provides long-lasting protection under various driving conditions

Specifications and approvals:

API SN
ACEA C2
PSA B71 2312
PSA 2290
FIAT 9.55535-DS1
FIAT GS1
CHRYSLER MS 90047
CHRYSLER 13340

HONDA
HYUNDAI
INFINITY
KIA
LEXUS
NISSAN
SUZUKI

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	50-70
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	9,3-12,5
Viscosity index	ASTM D 2270	-	> 160
Pour point	ASTM D 97	[°C]	< -35
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 7

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.