10.02.2025
v1

Technical Data for:

MARA EVOLUTION C2 5W-30

Description:
MARA EVOLUTION C2 5W-30 is fully synthetic engine oil for superior fuel economy, low CO2 emissions, excellent engine cleanliness, and aftertreatment system protection. Ideal for PSA Group engines with DPF and Japanese OEMs like Toyota, Honda, Subaru, and Nissan.

Benefits:
- Excellent wear resistance, extending engine life
- Helps reduce emissions due to its energy-conserving properties
- Provides long-lasting protection under various driving conditions

Specifications and approvals:

ACEA C2
API SN/CF
FIAT 9.55535-S1
FIAT S2
FIAT S3
FIAT T2
PSA B71 2290
MB 229.31
MB 229.51
BMW LL-04
PORSCHE A40
GM Dexos 2
GM LL-B-025
GM LL-A-025
FORD WSS-M2C917-A
FORD WSS-M2C50-A
JLR 03.5007
RENAULT RN0700
RENAULT RN0710
RENAULT RN17

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	50-70
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	9,3-12,5
Viscosity index	ASTM D 2270	-	> 160
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 9

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

Produced under licence of Mapetrol
Linhartova ulica 17A, 2000 Maribor, Slovenia, EU // lab@mapetrol.si // +386 2 230 28 80