Technical Data for:

MARA HIDROL HV 15

Description:
Mara Hidrol HV 15 is a high-quality hydraulic oil with a high viscosity index, which is used in conditions of various temperatures and pressures. They are intended for hydraulic systems that operate in open spaces, as well as other systems that are exposed to external influences.

Benefits:
- Ensures smooth operation of hydraulic systems, truck cranes, excavators, loaders, tippers and forklifts
- Great protection against wear and corrosion
- Good filterability
- Excellent thermal and oxidative stability even in the most demanding operating conditions

Specifications:
ISO 6743-4 (L-HV)/11158 (L-HV)
DENISON HF-0/HF-2
SPERY VICKERS M-2950-S/I-286-S
DIN 51524-3 (HVLP)
AFNOR NF E 48-603 (HV)

Typical characteristics:

Test	**Unit**	**Results**				
		15	**32**	**37**	**46**	**68**
Density at 15 °C	[g/cm3]	0.870	0.872	0.875	0.879	0.882
Kinematic viscosity at 40 °C	[mm2/s]	15	32	37	46	68
Viscosity index	-	145	145	140	140	140
Pour point	[°C]	-30	-30	-30	-27	-27
Flash point	[°C]	165	210	210	220	225

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children.