Technical Data for:

MARA TRANS GEAR EP SAE 90

Description:
MARA TRANS GEAR EP SAE 90 is multi-purpose mineral oil.

Benefits:
- Minimizes gear wear and prolongs the life of transmissions and differentials
- Reduces friction for smoother gear shifting and operation
- Protects against rust and corrosion, especially in harsh environments

Specifications and approvals:
API GL-5
ZF TE-ML 07A
ZF 08

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,85-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	135-150
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	14,0-16,0
Viscosity index	ASTM D 2270	-	> 90
Pour point	ASTM D 97	[°C]	< -20
Flash point (Cleveland)	ASTM D 92	[°C]	> 210

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

Produced under licence of Mapetrol
Linhartova ulica 17A, 2000 Maribor, Slovenia, EU // lab@mapetrol.si // +386 2 230 28 80