28.11.2025
v2

Technical Data for:

MARA TRANS GEAR EP SAE 75W-80

Description:
MARA TRANS GEAR EP SAE 75W-80 is transmission lubricant crafted from selectively chosen, highly refined base oils offers an exceptionally high viscosity index. It ensures excellent fluidity at low temperatures and extends the lifespan of both the oil and gears.

Benefits:
- Reduces friction, extending the lifespan of gears and other components
- Performs well at high temperatures, preventing breakdown in harsh conditions
- Corrosion protection
- Improves the performance of manual transmissions and differentials

Specifications and approvals:
API GL-5
ZF TE-ML 07A
ZF 08

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,82-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	45-70
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	8,5-11,0
Viscosity index	ASTM D 2270	-	> 150
Pour point	ASTM D 97	[°C]	< -40
Flash point (Cleveland)	ASTM D 92	[°C]	> 200

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.