Technical Data for:

MARA CLASSIC 2T

Description:
MARA CLASSIC 2T is a cost-effective mineral-based oil for air-cooled two-stroke gasoline engines. Ideal for older engines, scooters, agricultural machinery, motor testers, pumps, and small machines (up to 50cm³). Mix with gasoline as per manufacturer guidelines. Not suitable for water-cooled two-stroke engines.

Benefits:
- Excellent lubrication of engine components
- Minimizes wear
- Reduces deposit formation on spark plugs, preventing burnout
- Complete and instantaneous mixing with fuel

Specifications and approvals:
API TC
JASO FB
JASO FC

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,87-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	60-90
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	7-12
Viscosity index	ASTM D 2270	-	> 90
Pour point	ASTM D 97	[°C]	< -15
Flash point (Cleveland)	ASTM D 92	[°C]	> 70

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

Produced under licence of Mapetrol
Linhartova ulica 17A, 2000 Maribor, Slovenia, EU // lab@mapetrol.si // +386 2 230 28 80