TRANSMISSIONS

MOTOR VEHICLE LUBRICANTS

CEPSA ATF 6000 MV-S

DESCRIPTION

High-quality 100% synthetic multi-vehicle oil, developed to comply with the requirements of a broad range of automatic transmission manufacturers, in particular Asian manufacturers that require the JASO M315 Type 1A specification.

PRODUCT APPLICATIONS

- Recommended for use in transmissions operating under normal and very severe operating conditions.
- Formulated to meet the friction and viscosity requirements for transmissions and servos from Asian, American and European manufacturers.
- Suitable for use in hydraulic systems that require an oil with ATF characteristics.
- Do not use in CVT, Dexron® VI or Mercon® SP transmissions (consult the manufacturer's user manual for further details).

PRODUCT PERFORMANCE

- Exceptional cleaning of the transmission system.
- Its friction properties facilitate smooth operation of the gears, avoiding vibration problems and extending the life of the transmission.
- Excellent performance at high temperatures.
- Rapid circulation and outstanding lubrication at very low temperatures.
- The synthetic base oils help to ensure greater protection against varnishing, sludge and other undesirable deposits for the transmission.

SPECIFICATIONS

- JASO M315 Type 1A
- Subaru ATF
- Mitsubishi SP-III
- Hyundai
- Toyota T-IV
- Isuzu BESCO ATF-III
- HONDA ATF Z-1
- Ford MERCON®
- Nissan MATIC Fluid C/D/J
- G.Motors DIII-H
- Allison C-4

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA ATF 6000 MV-S
Density at 15ºC	Kg/l	D-4052	0.847
Flash point COC	ºC	D-92	>190
Pour point	ºC	D-97	-42
Viscosity at 100ºC	cSt	D-445	7.20
Viscosity at 40ºC	cSt	D-445	35.22
Viscosity index		D-2270	185
Brookfield viscosity – 40ºC	cSt	D-2983	<20000
Color		D-1500	Red

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes.
These values may be modified without any prior warning.