TRANSMISSIONS

MOTOR VEHICLE LUBRICANTS

CEPSA AURIGA LS PLUS 80W90

DESCRIPTION

Lubricant oil specially formulated for lubricating differentials that require oils with limited slip characteristics.

PRODUCT APPLICATIONS

- All types of differentials that require the indicated level of quality, especially of the "limited slip" type (L.S.)
- Good performance at high speed and high torque, with remarkable noise reduct.

PRODUCT PERFORMANCE

- Superb fluidity at low temperatures.
- Optimum anti-foam characteristics.
- Contains Extreme Pressure (EP) additives and friction improvers.
- Superb stability at high service temperatures.
- No problems with damage to rubber seals and the like.

SPECIFICATIONS

- API GL-5
- MIL-PRF-2105
- ZF TE-ML 05C/12C/21C[1]

[1] ZP -ZF001050

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA AURIGA LS PLUS 80W90
SAE grade			**80W90**
Density at 15ºC	Kg/l	D-4052	0.904
Flash point COC	ºC	D-92	210
Pour point	ºC	D-97	-25
Viscosity at 100ºC	cSt	D-445	14.2
Viscosity at 40ºC	cSt	D-445	129.8
Viscosity index		D-2270	107

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes.
These values may be modified without any prior warning.