28.11.2025
v2

Technical Data for:

MARA DOT 4

Description:
MARA DOT 4 is fluid intended for pressure transfer in hydraulic brake systems of all types of motor vehicles where the DOT-4 quality level is recommended.

Benefits:
- Handles extreme braking scenarios, making it ideal for performance or heavy-duty vehicles
- Performs better in high-temperature and high-pressure environments

Specifications and approvals:
ISO 4925 Class 4
SAE J 1704
SAE 1703
FMVSS 116 DOT4
H.Z2.100 tip 2

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	1,00-1,10
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	150-250
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	2,0-4,0
Viscosity index	ASTM D 2270	-	> 200
Pour point	ASTM D 97	[°C]	< -40
Flash point (Cleveland)	ASTM D 92	[°C]	> 200

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.