28.11.2025
v2

**Technical Data for:**

**MARA GARDEN SAE 30**

**Description:**
MARA GARDEN SAE 30 is mineral motor oil for four-stroke engines. It is used for air-cooled engines in motor mowers, compressors, denerators, cultivators and more.

**Benefits:**
- Ensures reliable performance
- Offers minimized wear and longer engine life
- Removes harmful deposits
- Offers protection in tough conditions
- Protects against rust and corrosion

**Specifications and approvals:**
API SJ/CF

**Typical characteristics:**

| Test | Method | Unit | Results |
|---|---|---|---|
| Density at 15 °C | ASTM D 4052 | [g/cm³] | 0,87-0,90 |
| Kinematic viscosity at 40 °C | ASTM D 445 | [mm²/s] | 85-100 |
| Kinematic viscosity at 100 °C | ASTM D 445 | [mm²/s] | 10-12 |
| Viscosity index | ASTM D 2270 | - | > 90 |
| Pour point | ASTM D 97 | [°C] | < -15 |
| Flash point (Cleveland) | ASTM D 92 | [°C] | > 220 |
| T.B.N. | ASTM D 2896 | mg KOH/g | > 6 |

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

**Storage:**
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

**Produced under licence of Mapetrol**
Linhartova ulica 17A, 2000 Maribor, Slovenia, EU // lab@mapetrol.si // +386 2 230 28 80