Technical Data for:

MARA EVOLUTION LONGLIFE 5W-30

Description:

MARA EVOLUTION LONGLIFE 5W-30 is a cutting-edge synthetic multigrade engine oil designed for lubrication of modern gasoline and diesel engines. Specifically engineered to meet exhaust emissions standards EURO IV, EURO V, and EURO VI. It's ideally suited for engines equipped with diesel particulate filters (DPF) or exhaust gas recirculation (EGR) systems. It represents the next generation of Low SAPS synthetic engine oils, meticulously crafted for the demands of modern Volkswagen Group engines (VW, Audi, Seat, Skoda). Tailored for fuel-injected petrol engines equipped with emissions control technologies such as catalytic converters, as well as high-performance turbocharged and intercooled direct diesel injection engines featuring exhaust gas recirculation and particulate filters.

Benefits:

- Exeptional lubrication
- Ensures unparalleled performance and environmental compliance
- Provides long engine life
- Ultimate performance and protection under all operating conditions

Specifications:

ACEA C3
VW 504 00/507 00
MB 229.51
BMW Longlife-04
Porsche C30

Typical characteristics:

Test	Unit	Results
Kinematic viscosity at 40 °C	[mm2/s]	57.9
Kinematic viscosity at 100 °C	[mm2/s]	10.1
Viscosity index	-	163
Pour point	[°C]	-39
Flash point	[°C]	220

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children.