Technical Data for:

MARA POWER RACING 2T

Description:
MARA POWER RACING 2T is fully synthetic oil designed for lubrication of modern two-stroke racing engines with air or water cooling. Suitable for all 2-stroke engines in modern Japanese and European motorcycles, scooters, ATVs and quads. This oil can be used for pre-mix, or with oil injection systems.

Benefits:
- Protects engine components from wear and tear during intense, high-speed operation
- Prevents oil breakdown under extreme temperatures, ensuring reliable performance during racing conditions
- Low-ash formula minimizes visible exhaust smoke and reduces environmental impact

Specifications and approvals:
API TC+
JASO FD
ISO-L-EGD

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,87-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	55-80
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	9,2-11,4
Viscosity index	ASTM D 2270	-	> 140
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 130

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

Produced under licence of Mapetrol
Linhartova ulica 17A, 2000 Maribor, Slovenia, EU // lab@mapetrol.si // +386 2 230 28 80