Technical Data for:

MARA GTX 700 5W-30

Description:
MARA GTX 700 5W-30 is designed for gasoline and diesel engines of a wide range of vehicles (cars, light SUVs, vans and light trucks) from European and other manufacturers.

Benefits:
- High shear stability
- Outstanding low temperature behavior
- Fuel efficiency and reduced pollutant emissions
- Enhanced wear resistance
- Optimal stability against aging
- Superior engine cleanliness
- Instant lubrication following a cold start

Specifications and approvals:
API SL/CF
ACEA A3/B4
MB 229.1
BMW Longlife 98
VW 505 00
VW 501 01

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	50-70
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	9,3-12,5
Viscosity index	ASTM D 2270	-	> 160
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 9

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.