10.02.2025
v1

Technical Data for:

MARA EVOLUTION LL 5W-30

Description:
MARA EVOLUTION LL 5W-30 is a synthetic engine oil designed for gasoline and diesel engines to provide ultimate performance and protection under all operating conditions and to protect Exhaust Emission Reduction Systems. Formulated for use in modern VW, Audi, Seat and Skoda gasoline and diesel engines.

Benefits:
- Exeptional lubrication
- Ensures unparalleled performance and environmental compliance
- Provides long engine life
- Ultimate performance and protection under all operating conditions

Specifications and approvals:
ACEA C3
VW 504 00
VW 507 00
MB 229.51
BMW Longlife-04
Porsche C30

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	50-70
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	9,3-12,5
Viscosity index	ASTM D 2270	-	> 160
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 9

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

Produced under licence of Mapetrol
Linhartova ulica 17A, 2000 Maribor, Slovenia, EU // lab@mapetrol.si // +386 2 230 28 80