Technical Data for:

MARA EVOLUTION MB 5W-40

Description:
MARA EVOLUTION MB 5W-40 is fully synthetic engine oil for gasoline and diesel car engines, excluding those with diesel particulate filters (DPF). Offers excellent engine protection, longer oil drain intervals, cleanliness, and low-temperature fluidity.

Benefits:
- Excellent wear protection, even under high-stress conditions
- Reduces friction, improving fuel economy
- Helps maintain the efficiency of the exhaust system, reducing emissions
- Designed for extended oil change intervals, offering stable performance throughout its life

Specifications and approvals:
ACEA A3/B4
API SN/CF
BMW LONGLIFE-01
MB 229.3
MB 229.5
PORSCHE A40
PSA B71 2296
RENAULT RN0700
RENAULT RN0710
VW 502 00
VW 505 00
FIAT 9.55535-M2
FIAT N2

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	75-95
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	12,5-16,3
Viscosity index	ASTM D 2270	-	> 160
Pour point	ASTM D 97	[°C]	< -36
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 7

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:
Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.