

LUKOIL GENESIS SPECIAL XFE 5W-30

synthetic engine oil for gasoline engines of GM

APPROVALS

GM dexos1™Gen2-licensed D10531HH072

MEETS REQUIREMENTS

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL XFE 5W-30 is a synthetic engine oil for up-to-date gasoline engines. It offers high reliability and allows maximum reduction of fuel consumption. The new additive technology protects not just the environment it also keeps the turbocharger and intercoolers clean.

LUKOIL GENESIS SPECIAL XFE 5W-30 was specially developed for the latest gasoline engines of GM to protect the engines from low speed preignition.

Due its special formulation **LUKOIL GENESIS SPECIAL XFE 5W-30** is not suitable for diesel engines.

LUKOIL GENESIS SPECIAL XFE 5W-30 minimizes wear by rapid oil circulation, especially in the warm-up phase of the engine, allowing maximum loads and provides exceptionally high safety reserves and long oil drain intervals.

APPLICATION

LUKOIL GENESIS SPECIAL XFE 5W-30 is recommended to use in gasoline engines requiring the specification GM dexos1™Gen2.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL XFE 5W-30
Density/15°C	kg/m ³	DIN 51575	848
Flash point COC	°C	ISO 2592	>220
Viscosity class	---	SAE J 300	5W-30
Viscosity/40°C	mm ² /s	DIN 51562/T1	62,4
Viscosity/100°C	mm ² /s	DIN 51562/T1	11,25
Viscosity index	---	DIN ISO 2909	176
Pour point	°C	DIN ISO 3016	-42

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

22 September 2017, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe GmbH
 Uferstrasse 8
 1220 Vienna, Austria

+43(1)205 222-8800
www.lukoil-lubricants.eu

member of:

