



## 02000B Motor Oil 10W-30 Multi Grade

Document version: November 29th 2017



### Description

This high-tech multi-grade motor oil has been developed for the lubrication of four stroke petrol- and diesel engines that are naturally aspirated and turbocharged. This motor oil provides total engine protection and excellent cold-cranking properties.

### According to the specifications of

ACEA A3/B4  
API CF / SL

### Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
02001B	1 L	6	450
02004B	4 L	4	112
EXP.02005B	5 L	4	-
02005B	5 L	4	112
02020B	20 L	1	30
02060B	60 L	1	12
02205B	205 L	1	2
02999B	1000 L	1	-
P02000B	bulk	1	-

## Typical characteristics

TEST	METHOD	VALUE	
SAE		10W-30	
Density at 15°C	ASTM D4052	0.875	kg/l
Kinematic viscosity at 40°C	ASTM D445	70.4	mm <sup>2</sup> /s
Kinematic viscosity at 100°C		10.9	mm <sup>2</sup> /s
Viscosity index	ASTM D2270	145	
Dynamic viscosity at -25°C	ASTM D5293	6700	mPa·s
Flashpoint COC	ASTM D92	237	°C
Pourpoint	ASTM D97	-39	°C
Total Base number	ASTM D2986	7.6	mgKOH/g
Sulphated ash	ASTM D874	0.85	mass%