



16000CVT CVT Constant Variable Transmission Special Fluid

Document version: 19 June 2017



Art. no.	Volume	Items per unit	Items per pallet
16001CVT	1 L	6	450
16004CVT	4 L	4	112
16020CVT	20 L	1	30
16060CVT	60 L	1	12
16205CVT	205 L	1	2
16999CVT	1000 L	1	0
P16000CVT	bulk	1	0

Description

This premium synthetic high grade CVT fluid is used in various CVT transmissions that make use of a push-belt or steel chain. This transmission oil has been specially developed for Mercedes-Benz A and B class and Multitronic transmissions of the VAG group.

Specifications

BMW 83 22 0 136 376 / 83 22 0 429 154
Chrysler CVT+4
Daihatsu AMIX CVTF-DC
Dodge CVT+4
Ford M2C928-A
GM DEX-CVT
Honda HCF-2
Jeep CVT+4
MB-Approval 236.20
Mitsubishi CVTF-J1 / CVTF-J4

Page 1/2

Nissan CVT Fluid NS-1 / CVT Fluid NS-2 / CVT Fluid NS-3
Subaru ECVT / i-CVT / Lineartronic CVTF
Suzuki CVT Green 1 / CVT Green 2
Toyota CVT FE / TC
VW G 052 180 / 052 516
VW TL 52 180 / 52 516

Typical characteristics

Density at 15°C	0,848	kg/l
Colour	Colour Barnstone (amber)	
Kinematic viscosity at 40°C	34.0	mm ² /s
Kinematic viscosity at 100°C	7.0	mm ² /s
Viscosity index	173	
Flashpoint COC	210	°C
Pourpoint	-52	°C
Brookfield viscosity at -40°C	11900	mPa·s